

Manufactured by Aqua Lung, the SSH provides the Military and Commercial Diver with a rugged working harness for any tended diving application. The Molle on/off feature of the weight system makes it ideal for cold or tropical conditions.

**“ NEW! SSH Can Now Integrate All APEKS WTX Buoyancy Cells (Not Shown).”**



**SureLock® Double Action Weight Release System**

**Molle on/off weight sheaths using Malice Clips®**

**Malice Clip®**

### SSH Features:

Durability, comfort and strength.

- Harness breaking strength = 1100 lbs
- D-rings breaking strength = 5000 lbs

*Note: Surpasses strength requirements set forth in ADCI Consensus Standards 2004*

Three Sizes - Fully Adjustable:

- Adjustable vertical webbing
- Adjustable waist
- Adjustable crotch strap

**SureLock® - Reliable weight release system**

- Molle on/off weight sheaths using Malice Clips®
- Double action release-prevents accidental weight release
- Carries up to 50 lbs
  - 20 lbs in both side weight pouches
  - 10 lbs in rear non-ditch pocket

Securely carries single EGS bailout cylinder (not included)

Extraction points

- Single point extraction D-Ring on back
- Two point extraction D-Rings on upper chest

Item Name	AL Part #	Notes
SSH Complete <i>Includes all items below</i>	Size 0 - 769158 Size 1 - 769161 Size 2 - 769169	Size 0 - waist 28" - 34" Size 1 - waist 32" - 40" Size 2 - waist 38" - 48"
20 lb SureLock® Wt. Pouch	769144	Refer to SSH Tech Manual for instructions
20 lb Double Action Wt Sheath	769159	Refer to SSH Tech Manual for instructions
Crotch Strap	Size 0 - 769186 Size 1 - 769163 Size 2 - 769184	Length = 31" Length = 37" Length = 44"
Tank band/Traction sleeves	769166	2 each
Universal Comfort Pad	769148	
Cylinder keeper	769164	
Malice Clips	769182	Refer to SSH Tech Manual for instructions

*The SSH may also be worn over the top of the Personal Dive Harness (PDH). When worn together, the SSH & PDH follows industry best practice whereby: positive control of the diver is maintained with the PDH while ditchable equipment that is secured to the SSH can be quickly removed during an emergency recovery. (PDH not shown. PN AMTC-H1305).*